

TECHNICAL DATASHEET:

Poly-Seal Adhesion Promoter

PRODUCT DESCRIPTION

H-O Poly-seal adhesion promoter facilitates application of Poly-seal butyl based flashing tapes in colder temperatures between 15°F to 35°F (-0°C to 2°C).

TYPICAL APPLICATIONS

- For cold-weather application of H-O poly-seal butyl based tapes.
- Excellent for preparing glass mat surfaces for bonding poly-seal tapes.

APPLICATION GUIDE:

- Surface must be clean, dry, and free of grease, oil or contaminants. USE IN WELL-VENTILATED AREA. Hold can 8 to 12 inches from surface. Spray light, even web coat. Use full arm movement, not just wrist. Keep can perpendicular to surface. Slightly overlap edges of spray pattern.
- For glass mat: apply an even coat, covering as much of surface as possible without excess dripping. Allow spray to set up 1-3 minutes depending on coating thickness, prior to applying tape.

CAUTION:

Do not puncture or incinerate can. Contents under pressure. FLAMMABLE - keep from flame. Do not expose to heat or store at temperatures above 110°F (43°C). Keep away from children. Goggles and gloves are recommended.

WARNING:

Contains Methylene Chloride (CAS #75-09-2), Propane (CAS #74-93-6), Isobutane (CAS #75-28-5). Methylene Chloride has been shown to cause cancer in certain laboratory animals, although there has been no evidence of it causing cancer in humans. Risk to health depends on level and duration of exposure. Use only in a well ventilated area. Keep away from heat and flame. Avoid prolonged exposure to vapor. Vapors harmful. Avoid direct contact with skin or eyes. May cause irritation. If inhalation causes irritation, remove individual to fresh air. In case of eye contact, flush thoroughly with running water for at least 15 minutes and get medical attention. This product contains a chemical known to the State of California to cause cancer. HARMFUL OR FATAL IF SWALLOWED.

LIMITED WARRANTY:

There are no warranties other than as set forth below and H-O Products neither assumes nor authorizes any person to assume any other obligations or liability in connection with this product. There are no implied or statutory warranties including the warranties of merchantability and fitness for particular purpose which extend beyond the warranty contained herein. H-O Products is not liable for incidental, consequential or special damages. This product is warranted to be free of any and all defects in workmanship and material at the time of shipment from our plant. H-O Products will replace or issue credit for original purchase price of material shown to be defective at the time of shipment.