

## TECHNICAL DATASHEET: SLM 360 Rubber Based Adhesive

### PRODUCT DESCRIPTION

SLM 360 is a double coated polyester (PET) film tape coated on both sides with an extremely aggressive rubber pressure sensitive adhesive. It is a versatile adhesive specially designed for difficult bonding applications and has excellent quick stick and shear properties.

### TYPICAL APPLICATIONS

- Permanent bonding applications on foams, plastics, metals and composite materials subjected to a broad range of environmental conditions

### PRODUCT FEATURES & BENEFITS

- Meets adhesive requirements of GM3622, CHRYSLER MS-CC211 and DELPHI SD2-324

TECHNICAL DATA	VALUE	TEST METHOD / STANDARD
ADHESIVE THICKNESS	1.5 mils	
ADHESIVE TYPE	Rubber	
ADHESIVE SYSTEM	Permanent Adhesive	
COLOR	Clear	
LINER	60# densified kraft	
PEEL ADHESION	96 oz/in	PSTC-101
MAXIMUM CONTINUOUS USE TEMPERATURE	180°F	
MINIMUM CONTINUOUS USE TEMPERATURE	-10°F	
GM3622	Pass	
DELPHI SD2-324	Pass	
CHRYSLER MS-CC211	Pass	

Specifications are believed to be accurate at the time of publication and are subject to change without notice. It is the responsibility of the end-user to test and determine suitability of this material for a particular application. **REV. 0**