

TECHNICAL DATASHEET: A463 Acrylic Transfer Adhesive Tape

PRODUCT DESCRIPTION

This adhesive is an unsupported permanent acrylic pressure sensitive adhesive that has excellent peel shear and tack properties.

TYPICAL APPLICATIONS

- Can be used to laminate and bond a wide variety of LSE materials and foams including polyolefins as well as ether and ester type polyurethanes.

PRODUCT FEATURES & BENEFITS

- Excellent adhesion to low surface energy materials
- High shear strength
- Great quick tack/fast wet out
- Biocide additive for enhanced microbial resistance

TECHNICAL DATA	VALUE	TEST METHOD / STANDARD
TOTAL THICKNESS	3.00 mils	PSTC-133
ADHESIVE TYPE	Acrylic	
ADHESIVE SYSTEM	Permanent Adhesive	
ADHESIVE SIDE	Single Sided	
COLOR	Clear	
LINER	76# moisture stable poly-coated kraft	
PEEL ADHESION	80 oz/in	PSTC-101
TACK	88 oz/in	ASTM D2979
SHEAR ADHESION @ 2.2 psi	168 hrs	PSTC 107
MINIMUM SERVICE TEMPERATURE	-40°F	
MAXIMUM SERVICE TEMPERATURE	250°F	

Specifications are believed to be accurate at the time of publication and are subject to change without notice. It is the responsibility of the end-user to test and determine suitability of this material for a particular application. H-O will provide samples for this purpose at no charge. **REV. 0**