

TECHNICAL DATASHEET: Cling Foam

PRODUCT DESCRIPTION

Industrial PVC foam cast to a high-gloss paper to achieve a foam surface that adheres to non-porous substrates, yet is removable and can be repositioned. It is available with adhesive so the foam can be laminated to cork or other substrates. It remains pliable at temperatures of -20°C to 78°C.

TYPICAL APPLICATIONS

- Spacer or temporary cushion for transportation
- Storage of non-porous materials such as glass

PRODUCT FEATURES & BENEFITS

- Very easy removal from glass
- Non-residue bonding system
- Can be used with a number of different substrates/materials

TECHNICAL DATA	VALUE	TEST METHOD / STANDARD
ADHESIVE THICKNESS	1/16"	
ADHESIVE TYPE	Cling Foam (PVC)	
ADHESIVE SYSTEM	Removable Adhesive	
COLOR	Ivory White	
ADHESION TO CORK	12 oz/in minimum	
ADHESION TO STAINLESS STEEL	12 oz/in minimum	
WATER ABSORPTION	3%	ASTM D1056
COMPRESSION DEFLECTION	5 psi	ASTM D1667
DUROMETER/HARDNESS (SHORE 00)	45	ASTM D2240
TENSILE STRENGTH	20 psi	ASTM D412 (DIE A)

NOTE: Foam without adhesive or liner unless noted. Specifications based on a sample size of three to five.

SHELF LIFE/STORAGE	
SHELF LIFE	Product shelf life begins on the date of production as referenced by the lot number: 6 months with adhesive and 2 years without adhesive when stored at or below 75°F.

Specifications are believed to be accurate at the time of publication and are subject to change without notice. It is the responsibility of the end-user to test and determine suitability of this material for a particular application. **REV. 0**