

TECHNICAL DATASHEET: 70 Durometer Commercial Grade Solid Neoprene

PRODUCT DESCRIPTION

70 durometer industrial grade solid neoprene, smooth finish, powder free.

TYPICAL APPLICATIONS

- Excellent for adhesive applications, window setting blocks, protective pads and isolation pads
- Glass carts, glass racks (base), shock absorption, vibration damping, and disparate metals isolation/insulation
- Great for isolation mounting and spacing

PRODUCT FEATURES & BENEFITS

- RoHS and REACH compliant
- Made in the USA

TECHNICAL DATA	VALUE	TEST METHOD / STANDARD
THICKNESS	1/32"	
COLOR	Black	
POLYMER	Polychloroprene	
TEMPERATURE RANGE	-30°F to 200°F	
DUROMETER/HARDNESS (SHORE A)	70 ±5	ASTM D2240
TENSILE STRENGTH (TYPICAL)	700 psi	ASTM D412
TENSILE STRENGTH (MINIMUM)	1,000 psi	ASTM D412
ELONGATION (TYPICAL)	200%	ASTM D412
ELONGATION (MINIMUM)	150%	ASTM D412
REACH	Yes	
ROHS	Yes	

Specifications are believed to be accurate at the time of publication and are subject to change without notice. It is the responsibility of the end-user to test and determine suitability of this material for a particular application. **REV. 0**