

TECHNICAL DATASHEET: Plain Cork MS113

PRODUCT DESCRIPTION

The ideal solution for no skid, no scratch protection of ceramic and porcelain products. Also used as spacers and for shipping glass "loose-light."

TYPICAL APPLICATIONS

- Book binding
- Cork bulletin boards
- Glass channels
- Packaging and sound absorption

PRODUCT FEATURES & BENEFITS

- Perfect, no-skid, non-scratch material
- Lightweight material and smooth to the touch
- Protection of ceramic and porcelain products

TECHNICAL DATA	VALUE	TEST METHOD / STANDARD
THICKNESS	1/32", 1/16", 3/32", 1/8", 3/16", 1/4"	
COLOR	Natural	
MATERIAL/SUBSTRATE	Plain Cork	
SPECIFIC WEIGHT	≥ 160 kg/m ³	ISO 7322
TENSILE STRENGTH	≥ 242 kPa	ISO 7322
COMPRESSIBILITY @ 100 PSI	35% - 55%	ISO 7322
RECOVERY @ 100 PSI	≥ 75%	ISO 7322
BOILING WATER	No disaggregation	ISO 7322
BINDER	Polyurethane	
CORK GRANULE SIZE	0.5 mm	

NOTE: • Other cork grades available by special request. Longer lead time, minimum orders will apply.

SHELF LIFE/STORAGE	
RECOMMENDED STORAGE CONDITIONS	20 ±3°C / 60 ±5% HR

Specifications are believed to be accurate at the time of publication and are subject to change without notice. It is the responsibility of the end-user to test and determine suitability of this material for a particular application. **REV. 0**