

TECHNICAL DATASHEET: Polyurethane Bumpers (Standard Durometer) SSB29

PRODUCT DESCRIPTION

Square feet provide the largest surface area of any pumper profile, which helps for heavier load bearing applications.

TYPICAL APPLICATIONS

- Square rubber bumper feet are commonly used on the bottom of larger appliances, picture frame corners, and on electronics as spacers.
- Can fit into a square cavity.

PRODUCT FEATURES & BENEFITS

- Manufactured in the USA.
- Easy peel-off application, non-staining, non-skidding and non-marring.
- Superior abrasion resistance, vibration and shock dampening.
- Superb coefficient of friction and resistance to skidding, crack resistant and resilient.

TECHNICAL DATA	VALUE	TEST METHOD / STANDARD
MATERIAL/SUBSTRATE	Polyurethane	
DUROMETER/HARDNESS (SHORE A)	60 - 70	
TENSILE STRENGTH	627 psi	
ELONGATION	192%	
TEAR STRENGTH	214 pli	
BASHORE REBOUND	27%	
ABRASION RESISTANCE	Excellent	
ABRASION RESISTANCE G/1,000 CYCLES TABOR H18, 1KG QUV, 500 HOURS	0.016	
UL-94 HBF	Pass	
ROHS	Pass	
FLAME RETARDANT	Yes	

NOTE: Tests were performed on hand mixed samples and the values are averaged.