

## TECHNICAL DATASHEET: Polyurethane Bumpers (Standard Durometer) SSB32

**PRODUCT DESCRIPTION**

Square feet provide the largest surface area of any pumper profile, which helps for heavier load bearing applications.

**TYPICAL APPLICATIONS**

- Square rubber bumper feet are commonly used on the bottom of larger appliances, picture frame corners, and on electronics as spacers.
- Can fit into a square cavity.

**PRODUCT FEATURES & BENEFITS**

- Manufactured in the USA.
- Easy peel-off application, non-staining, non-skidding and non-marring.
- Superior abrasion resistance, vibration and shock dampening.
- Superb coefficient of friction and resistance to skidding, crack resistant and resilient.

TECHNICAL DATA	VALUE	TEST METHOD / STANDARD
MATERIAL/SUBSTRATE	Polyurethane	
DUROMETER/HARDNESS (SHORE A)	60 - 70	
TENSILE STRENGTH	627 psi	
ELONGATION	192%	
TEAR STRENGTH	214 pli	
BASHORE REBOUND	27%	
ABRASION RESISTANCE	Excellent	
ABRASION RESISTANCE G/1,000 CYCLES TABOR H18, 1KG	0.016	
QUV, 500 HOURS	Slight yellowing	
UL-94 HBF	Pass	
ROHS	Pass	
FLAME RETARDANT	Yes	

**NOTE:** Tests were performed on hand mixed samples and the values are averaged.